

# Product Bulletin

## **Concept® 285 RoughMark™** **CONFORMABLE CALENDERED VINYL** **Removable Adhesive**

Concept®285 **RoughMark™** is a 90mic matte opaque polymeric vinyl film coated with a high-tack removable (HTR) acrylic pressure sensitive adhesive on a 135gsm layflat liner. The 135 gsm liner provides excellent dimensional stability for digital printing. Concept®285 accepts a variety of solvent-based, eco-solvent, latex and \*UV curable inks common to wide format digital printing systems.

### **Applications**

Concept®285 **RoughMark™** can be used in applications where a conformable removable vinyl is desired. This film conforms well with controlled heat and features clean removability from a variety of moderately textured substrates including brick, block, and concrete surfaces (vertical application only). If a high gloss finish is desired, it is recommended to use Concept®242 gloss clear cast laminate.

**NOTE:** If applied to a painted surface the paint must bond tightly to the substrate. Test all applications prior to use. Not designed for coated/ sealed/ treated stainless steel, brass or bronze surfaces

### **Thickness**

Film	90mic
Adhesive	45mic
Liner	135gsm
(Thickness variance +/- 10%)	

### **Temperature Ranges**

Minimum application temperature	+4,4°Celsius
Service temperature	-40°C to +93°C

### **Removability**

Removable up to 6 months for common substrates under normal exposure conditions.

### **Adhesion**

Stainless steel	18 N/25mm (FTM01)
-----------------	-------------------

Individual values may vary. Test thoroughly before production.

### **Water Resistance** **Humidity Resistance** **Storage Stability**

Excellent  
Excellent  
Good resistance to intermittent exposure from petroleum oils, grease, aliphatic hydrocarbons and gasoline.

### **Storage Stability**

One year shelf life when stored at 21°C and 50% relative humidity.

### **Product Series**

E285-54	1,37m x 50m
E285-5475	1,37m x 25m
E285-60	1,52m x 50m
E285-6075	1,52m x 25m

### **Recommendations**

Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation.

\* For UV Curable inks, please consult with the ink manufacturer for specifics on ink flexibility.



*General*  
**FORMULATIONS**

*Manufacturer of Pressure Sensitive Films, Traffic Graffiti  
Floor Advertising Films, Custom Coatings and Printing  
Inks.*

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537

Web Site: [www.generalformulations.com](http://www.generalformulations.com) • e-mail: [gfiinfo@generalformulations.com](mailto:gfiinfo@generalformulations.com)

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, including Disclaimer of Warranties and Limitation of Liability.