

Technical datasheet No.: 2017.10

Product: VALMEX®

AIRTEX® magic FR blockout

Article No.: 7565 5946

Type of coating and finish					
Type of coating	PVC	PVC			
Finish	both sides lacque	both sides lacquered (mat)			
Burning behaviour	DIN 4102: B1, EN	DIN 4102: B1, EN 13501-1: B-s1-d0			
for Burning behaviour	always check valid	always check validity of fire certificate, also check country-specific validity			
Total weight		350	g/m²	EN ISO 2286-2	
Tensile strength warp/weft		1200 / 1000	N/50 mm	EN ISO 1421/V1	
Tear strength warp/weft		130 / 80	N	DIN 53363	
Cold resistance		-20	°C	EN 1876-1	
High Temperature		+70	°C	PA 07.04 (intern)	
Crack resistance	no cracks	100000 x		DIN 53359 A	
Base fabric					
Material		PES		DIN EN ISO 2076	
Weave		L 1/1		ISO 3572	

These indicated technical data are based on average results. Due to production procedures deviations up to -5% can occur. All technical data are in accordance with the present standard of knowledge and give product information without legal binding. All data apply to new products. Applications suggested do not release the customer to test material for its intended application.

QM-071/3-08/00 EA/007-06/98 Date 29.07.2022