

### MAClite 4700

#### PRODUCT DESCRIPTION

MAClite 4700 is a commercial grade reflective film of beaded technology, providing wide-angle reflectivity of incident light and giving excellent night and day visibility. Given its up to 3 year outdoor durability, it is a cost-efficient choice for advertisements, emergency and highway maintenance vehicles and non-critical reflective signs. MAClite 4700 is available in multiple colours and the White Digital product is digitally printable.

**Face Material:** High gloss retroreflective film with glass microspheres:

White Digital: PVC/PET face film Colours: PET/acrylics face film

**Adhesive:** Permanent pressure sensitive adhesive. **Liner:** 150 gsm, one side polyethylene-coated white

kraft paper.

#### **TYPICAL USE**

MAClite 4700 is designed for 24h a day eye-catching decoration and identification in advertisements, highway maintenance vehicles and non-critical reflective signs. MAClite 4700 can be applied on flat surfaces.

#### **PROCESSING**

MACLite 4700 offers excellent weeding and cutting performance on a wide range of computer sign making equipment. All products can be screen printed and the White Digital product can be used on all digital printing platforms. However, a print test prior to application is strongly recommended. Print profiles are available for the White Digital product on most common printing platforms (Latex, UV, Solvent, Eco-Solvent).

MAClite 4700 does not require edge sealing.

#### Important remark

All surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination. The compatibility of paints and lacquers should be tested by the end-user, prior to use.

#### **SHELF LIFE**

1 year from date of purchase when stored at 20 to  $25^{\circ}$ C and  $\pm$  50-55% relative humidity.

# PHYSICAL PROPERTIES (TYPICAL VALUES) Average Values Test Method

Thickness Face film, White Digital (µm)	127-17	78	ISO 534		
	127-17	78	ISO 534		
	127-178		130 334		
Face film, Colours (µm)	127-178		ISO 534		
Adhesive data (N/i	nch)				
Peel on stainless ste	eel		FINAT FTM-1		
Initial	24.5				
24 hours	26.3				
Dimensional stability					
Shrinkage (48 hours at 70°C applied on Aluminium)	< 0.9mm		FINAT FTM-14		
Temperature ranges					
Application (°C)	18				
Service (°C)	- 23°C to + 65°C				
Solvent and chemi	cal re	esistance			
Water	No Effect		24 hours immersion		
Detergent	No Effect		24 hours immersion		
Gasoline	No Effect		1 hour immersion		

#### **EXPECTED DURABILITY**

White Digital, Blue, Red: Up to 3 years outdoor durability (vertical exposure)

Orange: Up to 2 years outdoor durability (vertical exposure)

Yellow: Up to 1 year outdoor durability (vertical exposure)

## Minimum Coefficient of Retroreflection (RA) (cd/lx/m2)

Observation Angle a	0.2°	0.33°			
Entrance Angle β1 (β2=0)	<b>-4</b> °	30°			
MAClite 4729-00 White Digital	50	6			
MAClite 4709-00 Yellow	25	3			
MAClite 4759-00 Red	8	1			
MAClite 4739-00 Blue	3	0.5			



#### DISCLAIMER

For more information on the durability and exposure please visit the "Mactac Technical Bulletin TB 7.5 Outdoor Durability of Mactac Graphics - Selfadhesive films" on the www.https://www.mactacgraphics.eu website.

Avery Dennison warrants that its Products meet its

specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see http://terms.europe.averydennison.com. Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting



from third party claims.