Why choose KernowJet MetaliK Permanent?

Enhance your graphics with our highly reflective metallic film, available in both silver and gold finishes. Engineered with a permanent adhesive backing, this premium film ensures long-lasting adhesion to a wide range of smooth surfaces while delivering a brilliant, mirror-like shine.

Our silver and gold metallic film are ideal for creating eye-catching signage, labels, packaging, displays, and branding materials. Perfect for both indoor and outdoor applications, this durable film combines exceptional clarity with a luxury metallic finish that elevates your designs and captures attention.

Whether you're producing retail graphics, premium product labels, luxury packaging or decorative accents, this reflective metallic film guarantees a professional, high-impact result that lasts.







Key Features

- High-tack permanent adhesive
- Turns any smooth surface into metallic
- Perfect for laminating to boards
- Very smooth finish, close to a mirror effect
- Corrosion free – 3 years outdoor UV stability

UK, EU & RoW Product List

PRODUCT DESCRIPTION	WIDTH	LENGTH	PRODUCT CODE
152µ KernowJet MetaliK Silver Permanent	1372mm 1524mm	45.7m	056SSI
152µ KernowJet MetaliK Gold Permanent	1372mm 1524mm	45.7m	056SGO

US Product List

PRODUCT DESCRIPTION	WIDTH	LENGTH	PRODUCT CODE
6.0mil KernowJet MetaliK Silver Permanent	54" 60"*	50' 150' 150'	056SSI
6.0mil KernowJet MetaliK Gold Permanent	54" 60"*	50' 150' 150'	056SGO

KERNOW COATINGS

KERNOWJET METALIK PERMANENT

PVC FREE

KERNOW COATINGS

PVC FREE

KERNOWJET®
LATEX, SOLVENT & UV

KernowJet MetaliK Permanent (PET)

Applications

- High-end product labels
- Signage and branding
- Point-of-sale materials
- Corporate and retail interiors
- Event & stage design
- Industrial safety labels

Compatibility

Latex	★★★
(Eco) Solvent	★★★
UV	★★★
Certified	Certified for HP Latex Inks

Property	**Typical Value** 056SSI/ 056SGO	**Units**
Construction		
Total Thickness	152 +/- 8 6.0 +/- 0.3	**µ/mil**
Total Weight	196 +/- 8	**gsm**
Face Material(without adhesive)		
Thickness	70 +/- 4 2.8 +/- 0.2	**µ/mil**
Weight	90 +/- 5	**gsm**
Adhesive		
Thickness	22+/-5 0.9+/-0.2	**µ/mil**
180° Peel Adhesion (SS)	21 - 23	**N/25mm**
Adhesive Application Temperature	+5 to +50 +41 to +142	**°C °F**
Adhesive Service Temperature	-40 to +180 -40 to +356	**°C °F**
PET Filmic Release Liner		
Liner Thickness	60 +/- 3 2.4 +/- 0.1	**µ/mil**
Liner Weight	83 +/- 2	**gsm**

1 PET

Recommended conditions:

Printroom	10°C - 30°C (50°F - 86°F)	30% - 65% RH
Usage	-40°C - 180°C (-40°F - 356°F)	10% - 90% RH
Storage	10°C - 20°C (50°F - 68°F)	20% - 50% RH

Please return unused product to its original packaging.
Shelf Life: 24 months after delivery (under recommended storage conditions).

Cleaning:

The film can be cleaned with a microfiber cloth or commercially available cleaning agents.

Cleaning aids or agents used should be non-abrasive and free of aggressive solvents.

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted.
We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application.
Regional certification differences apply.

Version 1, Copyright Sensitisers Group 2025