Why choose KernowJet MetaliK Removable?

Bring brilliance to your designs with KernowJet MetaliK® Removable, the premium choice for eye-catching graphics that shine as bright as real metal. Available in stunning mirror-like Silver & Gold finishes, this versatile film delivers the same dazzling effect on both sides – perfect for windows, displays and double-sided applications.

Designed with a removable adhesive, KernowJet MetaliK® Removable is easy to apply, reposition and peel away cleanly without residue, making it ideal for temporary signage, seasonal promotions and short-term décor. Its smooth, near-mirror surface ensures a flawless, professional look, while excellent cutting and weeding properties save time in production.







Key Features

- Same colour effect on both sides
- Removable adhesive, perfect for wet-application
- Cuts perfectly, weeds easily
- Very smooth finish, close to mirror effect
- Corrosion free for outdoor durability
- Silver film up to 3 years outdoor use without fade, Gold 1 year outdoor use

UK, EU & RoW Product List

PRODUCT DESCRIPTION	WIDTH	LENGTH	PRODUCT CODE
145µ KernowJet Metalik Removable Silver (PET)	1372mm 1524mm	45.7m	054CSI
145µ KernowJet Metalik Removable Gold (PET)	1372mm 1524mm	45.7m	054CGO

US Product List

PRODUCT DESCRIPTION	WIDTH	LENGTH	PRODUCT CODE
5.7mil KernowJet Metalik Removable Silver (PET)	54″	50′ 150′	054CSI
	60″*	150′	
5.7mil KernowJet Metalik Removable Gold (PET)	54″	50′ 150′	054CGO
	60″*	150′	

KERNOW COATINGS

KERNOWJET METALIK REMOVABLE

PVC FREE

KERNOW COATINGS

PVC FREE

KERNOWJET®
LATEX, SOLVENT & UV

KernowJet MetaliK Removable (PET)

Applications

- Temporary signage for trade shows, fairs and conferences
- Window graphics & seasonal promotions
- Trade shows and exhibtion graphics
- Shelf strips, price tags & display highlights
- Branded decals
- Mirror-finish accents in hotels, bars & restaurants

Compatibility

Latex	★★★
(Eco) Solvent	★★★
UV	★★★
Certified	Certified for HP Latex Inks

	Typical Value	Units
Property	054CGO/ 054CSI	
Construction		
Total Thickness	145 +/- 8 5.7 +/- 0.3	**µ/mil**
Total Weight	196 +/- 8	**gsm**
Face Material(without adhesive)		
Thickness	70 +/- 4 2.8 +/- 0.16	**µ/mil**
Weight	90 +/- 5	**gsm**
Adhesive		
Thickness	15.0+/-3 0.6+/-0.1	**µ/mil**
180° Peel Adhesion (SS)	8 +/- 1.5	**N/25mm**
Adhesive Application Temperature	+5 to +50 +41 to +142	**°C °F**
Adhesive Service Temperature	-40 to +180 -40 to +356	**°C °F**
PET Filmic Release Liner		
Liner Thickness	60 +/- 3 2.4 +/- 0.1	**µ/mil**
Liner Weight	83 +/- 2	**gsm**

1 PET

Recommended conditions:

Printroom	10°C - 30°C (50°F - 86°F)	30% - 65% RH
Usage	-40°C - 180°C (-40°F - 356°F)	10% - 90% RH
Storage	10°C - 20°C (50°F - 68°F)	20% - 50% RH

Please return unused product to its original packaging.
Shelf Life: 24 months after delivery (under recommended storage conditions).

Cleaning:

The film can be cleaned with a microfiber cloth or commercially available cleaning agents.

Cleaning aids or agents used should be non-abrasive and free of aggressive solvents.

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted.
We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application.
Regional certification differences apply.

Version 1, Copyright Sensitisers Group 2025