

FLAT DOT GLOSSY

(ZSO550)

GENERAL PROPERTIES

- Dot adhesive technology, Semi-removal adhesive and Glossy surface PVC Calendared film
- Bubble-free, dry application & Easy to install
- Excellent printability and outdoor durability (2 years)
- Repositionable during installation and Removable after installation with no residue
- Eco-solvent, Solvent, UV, Latex ink compatibility

* Application Guidelines

- Recommended for outdoor and indoor applications (* Recommend lamination to keep printed surface from fading)
- Recommended to test with projected conditions and location prior to full installation
- Clean mounting surface prior to applying this film
- Set up appropriate heating temperature to prevent curling with HP Latex printers

Specifications

Length (ft)	164	Width (inch)	54
Weight (gsm)	245	Coating	Resin
Caliper (mil)	5.8	Base Material	PVC
Inner Core (inch)	3	Printer	ESL UV
Surface	Glossy		

KEY FEATURES

- Bubble free, Dot adhesive technology
- Easy to install and removable without residue
- Excellent Durability
- Outstanding Printability

Application

- Indoor and outdoor, industrial advertising, promotion/exhibition hall printings, car advertising (taxi, bus, etc.)
- Application surfaces: Windows, Acrylic, Flat or compound/curved surfaces, rivets, etc.
- Non-applicable surfaces: Right-angle, weak painted wall, embossed surface, etc.

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.
(Humidity 35 ~ 65% RH)
- Shelf Life : One year, stored in original packing at recommended temperature
(Coating warranty guaranteed for 6 months from date of purchase)

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- **ICC Profiles are available** by calling the above number.

