

PGM Magnetic mat

Size: Isotropic/20M×1000×0.40mm/MUV/2.0mm Pole pitch/Matte white pvc

Dimensions: & Tolerance:

Item	Length	Width	Thickness	Thickness of PVC
	(m)	(mm)	(mm)	(mm)
Size	20	1000	0.40	0.13
Tolerance	0/+0.6	-1/+5	±0.04	±0.01

Magnetic Properties:

Code	Br(Gs)	Hcb(Oe)	Hcj(Oe)	(BH)max (MGOe)
Isotropic	≥1400	≥1000	≥1600	0.50-0.65

Pull Strength:

Code	Thickness (mm)	Pole pitch (mm)	Pull (g/cm ²)
Isotropic	0.40	2.0	≥17

Storage:

For reference, it works within the range of - 20 °C to+70 °C of the ambient temperature, and the customer needs to test the actual application environment

Storage Condition: 25°C and 50% humidity conditions

Shelf life: 12 months under original packaging condition

The magnetic force is permanent and will not degrade in normal temperature without strong magnetic interference.

Packing :

Scandraft AB

Headoffice
Företagsvägen 4
435 33 Mölnlycke
Sweden

Sales/Warehouse
Svarvarvägen 14C
142 50 Skogås
Sweden

Phone
+46 (0)31-68 69 30

Co. Reg. No.
556254-8361

E-mail
info@scandraft.se



in carton



in pallet (quantity per pallet will be as actual)

Scandraft AB

Headoffice
Företagsvägen 4
435 33 Mölnlycke
Sweden

Sales/Warehouse
Svarvarvägen 14C
142 50 Skogås
Sweden

Phone
+46 (0)31-68 69 30

Co. Reg. No.
556254-8361

E-mail
info@scandraft.se